



# SPEEDHIDE® zero

6-4900XI

Architectural Coatings

## GENERAL DESCRIPTION

PPG SPEEDHIDE zero Interior Latex Sealer is a professional grade zero-VOC\*\* interior acrylic primer formulated to meet the performance requirements of professional applicators. SPEEDHIDE zero Interior Latex Sealer can be used as a primer under alkyd or latex finish coats and is ideal under a variety of finishes. This zero-VOC\*\*, low-odor paint is ideal for painting occupied spaces while delivering the durable product performance required. It provides excellent sealing properties. Recommended for use on properly prepared interior wallboard and drywall surfaces, wood, and oriented strand board or particle board, and masonry.

## RECOMMENDED SUBSTRATES

Gypsum Wallboard-Drywall	Particle Board	Wood
Oriented Strand Board	Masonry	

## CONFORMANCE STANDARDS

- ✓ VOC compliant in all regulated areas
- ✓ Can earn LEED® 3.0 credits
- ✓ Meets GREENGUARD® Indoor Air Quality and GREENGUARD Children & Schools
- ✓ Meets the Collaborative for High Performance Schools (CHPS) Low-Emitting Materials criteria section 01350
- ✓ MPI® approval in category #50, Primer Sealer, Latex Interior
- ✓ MPI approval in category #149, Latex Interior Institutional Low Odor/VOC Flat (MPI Gloss Level 1)
- ✓ Meets MPI Green Performance Standards (GPS-1 and GPS-2)
- ✓ MPI approval in category #50 X-Green
- ✓ MPI approval in category #149 X-Green

## APPLICATION INFORMATION

Stir thoroughly. When using more than one container of the same color, intermix to ensure color uniformity. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

**Application Equipment:** Apply with a high quality brush, roller, paint pad, or by airless spray equipment. Where necessary, apply a second coat.

**Airless Spray:** Pressure 2000 psi, tip 0.015" - 0.021"

Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

## FEATURES / BENEFITS

### Features

- 0 g/L VOC\*\*
- Low odor
- Fast drying
- Great adhesion
- Excellent sealing properties
- Great enamel holdout
- Soap and water clean-up
- MPI approved
- Can earn LEED 3.0 credits

### Benefits

- Meets the most stringent environmental regulations nationwide
- Ideal for painting in occupied spaces
- Same day topcoat turning jobs faster
- Improves durability of finish
- Provides a uniform finish
- Promotes even sheen in topcoats
- Safe waterborne formula
- Meets strict performance and aesthetic requirements
- Contributes to sustainable design

SPEEDHIDE zero Interior Zero-VOC\*\* Latex Sealer

## APPLICATION INFORMATION (continued)

**Brush:** Polyester/Nylon Brush

**Roller:** 3/8" - 3/4" nap roller cover

**Thinning:** Thinning is not usually required. If necessary, thin with up to 1/4 pint (118mL) of water per U.S. gallon (3.78 L) of paint.

### Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 90°F	10 to 32°C
Substrate:	50 to 90°F	10 to 32°C

## PRODUCT DATA

**PRODUCT TYPE:** 100% Acrylic Latex

**SHEEN:** Flat

**VOLUME SOLIDS:** 35% +/- 2%

**WEIGHT SOLIDS:** 50% +/- 2%

**VOC\*\*:** 0 g/L (0 lbs./gal.)

**WEIGHT/GALLON:** 10.8 lbs. (4.9 kg) +/- 0.2 lbs. (91 g)

**COVERAGE:** Approximately 400 sq. ft./gal. (37 sq. m/3.78L) per U.S. Gallon (3.78L) on smooth, nonporous surfaces.

Wet Film Thickness: 4.0 mils

Wet Microns: 102

Dry Film Thickness: 1.4 mils

Dry Microns: 36

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

**DRYING TIME:** Dry time @ 77°F (25°C); 50% relative humidity.

To Touch: 30 minutes

To Recoat: 4 hours

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

**CLEANUP:** Clean tools with warm soapy water.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** Over 200°F (93°C)

\*\*Colorants added to this base paint may increase VOC level significantly depending on color choice.

