



**SHERWIN  
WILLIAMS.**



107.10

**PREPRITE®**  
Interior/Exterior Latex  
Block Filler  
B25W25

As of 03/04/2015, Complies with:		
OTC	Yes	LEED® 09CI Yes
SCAQMD	Yes	LEED® 09NC Yes
CARB	Yes	LEED® 09CS Yes
CARB	Yes	LEED® H & S Yes
MPI	Yes	NGBS Yes

CHARACTERISTICS	SPECIFICATION	SURFACE PREPARATION
<ul style="list-style-type: none"> <li>Allows topcoat on concrete block to be smooth and uniform</li> <li>Effective on above-grade, unpainted masonry surfaces</li> </ul> <p><b>Use on unpainted:</b></p> <ul style="list-style-type: none"> <li>Masonry</li> <li>Concrete</li> <li>Cement</li> <li>Flat Surfaced Concrete Block</li> </ul> <p><b>Color:</b> Off White  <b>Coverage:</b> 75-125 sq ft/gal  @ 16 mils wet; 8 mils dry</p> <p><b>Drying Time, @ 77°F, 50% RH:</b>  temperature and humidity dependent</p> <p>Touch: 2 hours  Recoat with latex based: 18 hours  Recoat with solvent based: 48 hours</p> <p><b>Flash Point:</b> N/A  <b>Finish:</b> 0-5 units @ 85°</p> <p><b>Vehicle Type:</b> Vinyl Acrylic  <b>White B25W00025</b></p> <p><b>VOC (less exempt solvents):</b>  &lt;50 g/L; &lt;0.42 lb/gal  As per 40 CFR 59.406 and SOR/2009-264, s.12</p> <p><b>Volume Solids:</b> 48 ± 2%  <b>Weight Solids:</b> 68 ± 2%  <b>Weight per Gallon:</b> 13.5 lb  <b>WVP Perms (US)</b>  grains/(hr ft<sup>2</sup> in Hg)</p>	<p><b>Masonry, Concrete, Cement, Block</b>  1 ct. PrepRite Block Filler  2 cts. Appropriate topcoat</p> <p><b>Recommended Architectural Topcoats</b>  A-100 Exterior Latex  Loxon Acrylic Coating  SuperPaint Exterior  Duration Exterior  Duration Home  ProClassic Interior  ProMar Interior  SuperPaint Interior</p> <p><b>Recommended Industrial Topcoats</b>  Pro Industrial DTM Acrylic  Industrial Enamel  Metalatex Semi-Gloss  Water Based Catalyzed Epoxy</p> <p>Other topcoats may be appropriate.</p> <p>Industrial topcoats have been tested for interior use only. PrepRite Block Filler has not been tested in environments subject to chemical attack. Any recommendations for use in such areas must follow a thorough evaluation of the effects of the environment on the PrepRite Block Filler and topcoat system.</p>	<p><b>WARNING!</b> Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p><b>Masonry, Concrete, Cement, Block</b>  Remove all surface contamination, form release agents, moisture curing membranes, etc. by washing with an appropriate cleaner, rinse and allow to dry. Pressure wash the surface if needed. Remove existing peeled or checked paint to a sound surface. Concrete and mortar must be cured, generally 30 days, at 75°F before painting.</p> <p>Complete removal of sealers, release compounds, and to provide a profile, tilt-up and poured-in-place concrete could require sandblasting or cleaning with commercial detergents. <b>Do not apply to smooth, slick surfaces, peeling may result.</b></p> <p>Masonry surfaces must be dry before priming. Moisture content must be 15% or lower, and the pH between 6 and 9. If the pH is greater than 9, use Loxon Block Surfacer in place of PrepRite Block Filler.</p> <p>For repairing <u>exterior</u> cracks, bugholes, air pockets, and other voids use an elastomeric patch or seal.</p>



**SHERWIN  
WILLIAMS.**

107.10

**PREPRITE®**  
Interior/Exterior Latex  
Block Filler  
B25W25

<b><u>SURFACE PREPARATION</u></b>	<b><u>APPLICATION</u></b>	<b><u>CAUTIONS</u></b>
<p><b>Mildew</b> Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p>	<p>Apply at temperatures above 50°F. No reduction necessary.</p> <p><b>Brush</b> - Use a nylon/polyester brush. <b>Roller</b> - Use a 3/8" to 1-1/2" nap cover. <b>Spray - Airless</b> Pressure.....2300 psi Tip .....028" Reduction.....as needed up to 1 pt/gal Remove all in-line and gun filters</p> <p>Spray application may be backrolled to work material into the surface. All application methods may be squeegeed to provide a very smooth surface.</p>	<p>For interior and exterior use. Must be topcoated for exterior use. Protect from freezing. Do not apply to damp or wet surfaces.</p> <p><b>CAUTION</b> contains <b>CRYSTALLINE SILICA</b>. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (<b>NIOSH</b> approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (<b>NIOSH</b> approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. <b>FIRST AID</b>: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. <b>DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE</b>. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. <b>WARNING</b>: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. <b>DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN</b>.</p>
	<p><b>CLEANUP INFORMATION</b></p> <p>Clean spills and spatters, hands and tools immediately with soap and warm water. After cleaning, flush spray equipment with compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.</p>	<p>HOTW 03/04/2015 B25W00025 39 44 FRC</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit <a href="http://www.paintdocs.com">www.paintdocs.com</a> to obtain the most current version of the PDS and/or an SDS.</p>