

**SHERWIN
WILLIAMS.**

As of 1/13/2015, Complies with:		
OTC	Yes	LEED® 09 CI Yes
SCAQMD	Yes	LEED® 09 NC Yes
CARB	Yes	LEED® 09 CS Yes
CARB SCM 2007	Yes	LEED® H Yes
MPI Spec #	No	NGBS Yes

PROCLASSIC®**Waterborne Interior Acrylic
Semi-Gloss
B31-1100 Series****CHARACTERISTICS**

ProClassic Waterborne Interior Acrylic Enamel is a high quality coating that provides a durable, non-yellowing finish. The excellent flow and leveling characteristics result in a smooth, rich finish equal to an alkyd enamel.

Project Uses

- trim areas and molding
- cabinets/doors/windows
- kitchen's/baths/locker rooms
- laundry rooms
- high traffic areas

Substrates

- drywall/plaster
- paneling/wood
- metal
- concrete/masonry
- wallcovering

Color:

Most colors

To optimize hide and color development, always use the recommended P-Shade primer

Coverage: 350 - 400 sq ft/gal

@ 4 mils wet; 1.3 mils dry

Drying Time, @ 77°F, 50% RH:

Touch:	1 hour
Recoat:	4 hours

Drying and recoat times are temperature, humidity, and film thickness dependent

Finish: 35 - 45 units @ 60°**Flash Point:** N/A**Tinting with CCE:**

Base	oz/gal	Strength
------	--------	----------

Extra White 0-5 Special

Deep Base 4-12 100%

High Ref White 0-5 100%

Vehicle Type: Styrene Acrylic**B31W01151****VOC (less exempt solvents):**

<50 g/L; 0.42 lb/gal

As per 40 CFR 59.406 and SOR/2009-264, s.12

Volume Solids: 33 ± 2%**Weight Solids:** 46 ± 2%**Weight per gallon:** 10.2 lb**SPECIFICATIONS****Block**

1 ct. Loxon Block Surfacer
2 cts. ProClassic Waterborne Interior Acrylic

Drywall

1 ct. Premium Wall & Wood Primer
2 cts. ProClassic Waterborne Interior Acrylic

Plaster

1 ct. Premium Wall & Wood Primer
2 cts. ProClassic Waterborne Interior Acrylic

Masonry

1 ct. Loxon Concrete & Masonry Primer
2 cts. ProClassic Waterborne Interior Acrylic

Metal - Steel, Aluminum, Galvanized

1 ct. All Surface Enamel Latex Primer
2 cts. ProClassic Waterborne Interior Acrylic

Wood, Composition Board

1 ct. Premium Wall & Wood Primer
2 cts. ProClassic Waterborne Interior Acrylic

Other primers may be appropriate.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer/sealer.

Drywall

Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry, Concrete, Block

All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer.



**SHERWIN
WILLIAMS.**

101.36a

PROCLASSIC®
Waterborne Interior Acrylic
Semi-Gloss
B31-1100 Series

SURFACE PREPARATION	APPLICATION	CAUTIONS
Plaster Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.	Apply at temperatures above 50°F. No reduction necessary.	For interior use only. Protect from freezing. Non-photochemically reactive.
Wood Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.	Brush Use a nylon/polyester brush. Roller Use a 1/4"-3/4" nap synthetic roller cover. Spray—Airless Pressure..... 2000 psi Tip015"- .021" Tip for fine finishing011"	LABEL CAUTIONS CAUTION contains CRYSTALLINE SILICA Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.
Mildew Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.	Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with compliant solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.	HOTW 1/13/2015 B31W01151 14 31 Viet
Caulking Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.	CLEANUP INFORMATION	
<p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit www.paintdocs.com to obtain the most current version of the PDS and/or an MSDS.</p>		